

## Alps series filters

### MODEL

### AF260

Filter capacity	l/min	4333	Flow rates at 7 bar and 20°C QF - Dust Filtration PF - General purpose Protection Filtration HF - High Efficiency Oil Removal Filtration CF - Activated Carbon Filtration
	m³/h	260	
Working pressure	bar	7 (17 max)	
Air connections	IN/OUT	1" BSP	
Net weight	Kg	2,1	
Standard type of drain	None		

Filtration grade		QF	PF	HF	CF
Complete filter code		04A.0260AQG03	04A.0260APG03	04A.0260AHG03	04A.0260ACG03
Filter element code		04E.0260AQ	04E.0260AP	04E.0260AH	04E.0260AC
Physical filtration process		Interception	Interception+coal escing	Interception+coal escing	Adsorption
Max solid dimension intercepted (ISO 8573-1)	µm	1 µ	0,1 µ	0,01 µ	//
Max solid dimension intercepted (ISO 8573-1)	Class	3	2	1	//
Remaining oil content after filtration (ISO 12500-1)	mg/m³	//	0,1 mg/m³	0,01 mg/m³	0,003 mg/m³
Remaining oil content after filtration (ISO 12500-1)	Class	//	2	1	//
Max temperature	°C	100	100	100	60
Pressure drop with new element	bar	0,045	0,05	0,05	0,035
Pressure drop with saturated elements	bar	0,11	0,11	0,11	0,11
Element replacement time	hours	4000 h	4000 h	4000 h	1000 h
Element replacement time	months	6	6	6	3

Line pressure [bar]	1	2	3	5	7	9	11	13	15	17
Correction factor	0,38	0,53	0,65	0,85	1,00	1,13	1,25	1,36	1,46	1,56

