

REFRIGERATED COMPRESSED AIR DRYER

MODEL:

ED24000W 400/3/50

Rated capacity*





Flow rate	m ³ /h l/min cfm	24000 400000 14125,9	
Inlet air temperature	°C / °F	35 / 95	(Max 55 / 131)
Outlet air temperature	°C / °F	27 / 81	(Max 40 / 104)
Water temperature	°C / °F	29,4 / 84	(Max 35 / 95)
Water consumption	m ³ /h	30,4	(Max 38)
Working pressure	bar / psi	7,0 / 102	(Max 13 / 189)
Pressure drop	bar / psi	0,30 / 4,4	(Max 0,34 / 4,9)
Pressure dew point	°C / °F	3 / 37	
Power supply	V/Ph/Hz	400/3/50	(±10% / -- / ±1)
Rated power consumption	kW	2 x 16,26	(Max 2 x 29,03)
Rated adsorption	A	2 x 30,35	(Max 2 x 47,19)
Lock Rotor Ampere	A	2 x 270	
Weight	Kg / Lbs	2490 / 5.490	
Air connections	IN/OUT	2 x DN 200 PN16	
Water connections	IN/OUT	2 x 2" BSP	
Water pressure	bar / psi	Min. 2 / 29 - Max. 10 / 145	
Ambient temperature	°C / °F	25 / 77	(Max 46 / 155)
Coolant type	Freon	R407C	

Standard features

Control panel:	<i>Electronic system type</i>	Separator type:	<i>Demister type</i>
Condenser:	<i>Water cooled, shell and tube</i>	Compressor type:	<i>Hermetic type</i>
Water flow regulator:	<i>Pressostatic valve</i>	Installation location:	<i>Indoor</i>
Heat exchanger:	<i>Aluminium brazed plate</i>	Drain discharge:	<i>No loss drain</i>
Expansion method:	<i>Capillary tube + by-pass</i>	Electric protection:	<i>IP 42</i>

* Performances refer to air suction of FAD 20°C (68°F), 1 bar (14.5 psig), and the following operating conditions: 7 bar (100 psig) working pressure, 3°C (37°F) pressure dewpoint, 29.4°C (84.9°F) water temperature, 35°C (95°F) compressed air inlet temperature.

Performances & specifications: +/- 5%

	Air in		Power supply		WI	Water in
	Air out		Condensate outlet		WO	Water out

