

Standard filters
MODEL
F0280

Filter capacity	I/min m³/h	28000 1680	Flow rates at 7 bar and 20°C
Working pressure	bar	7 (16 max)	QF - Dust Filtration
Air connections	IN/OUT	3" BSP	PF - General purpose Protection Filtration
Net weight	Kg	6,7	HF - High Efficiency Oil Removal Filtration
Standard type of drain	Manual		CF - Activated Carbon Filtration
			DF - Dust filtration (10 µ)

Filtration grade	QF	PF	HF	CF
Complete filter code	04A.1680.QG00	04A.1680.PG00	04A.1680.HG00	04A.1680.CG00
Filter element code	04E.1680.Q	04E.1680.P	04E.1680.H	04E.1680.C
Physical filtration process	Interception	Interception+coal escing	Interception+coal escing	Adsorption
Max solid dimension intercepted (ISO 8573-1)	µm	5 µ	1 µ	0,01 µ
Max solid dimension intercepted (ISO 8573-1)	Class	3	2	1
Remaining oil content after filtration (ISO 12500-1)	mg/m³	//	0,1 mg/m³	0,01 mg/m³
Remaining oil content after filtration (ISO 12500-1)	Class	//	2	1
Max temperature	°C	100	100	100
Pressure drop with new element	bar	0,05	0,1	0,1
Pressure drop with saturated elements	bar	0,6	0,6	0,6
Element replacement time	hours	4000 h	3500 h	3500 h
Element replacement time	months	6	5	5
				4

Line pressure [bar]	1	2	3	5	7	9	11	13	15	16
Correction factor	0,20	0,36	0,50	0,75	1,00	1,25	1,50	1,75	2,00	2,13

