



## TECHNICAL DATA SHEET

Rev.00 - 24/11/2015

### Standard filters

#### MODEL

#### F2500

|                        |               |                 |   |
|------------------------|---------------|-----------------|---|
| Filter capacity        | I/min<br>m³/h | 236667<br>14200 | Flow rates at 7 bar and 20°C                |
| Working pressure       | bar           | 7 (16 max)      | QF - Dust Filtration                        |
| Air connections        | IN/OUT        | DN200 BSP       | PF - General purpose Protection Filtration  |
| Net weight             | Kg            | 530             | HF - High Efficiency Oil Removal Filtration |
| Standard type of drain | Manual        |                 | CF - Activated Carbon Filtration            |
|                        |               |                 | DF - Dust filtration (10 µ)                 |

| Filtration grade                                     | QF            | PF                          | HF                          | CF            |
|--|---------------|-----------------------------|-----------------------------|---------------|
| Complete filter code                                 | 04F.A142.QG00 | 04F.A142.PG00               | 04F.A142.HG00               | 04F.A142.CG00 |
| Filter element code                                  | 04E.A142.Q    | 04E.A142.P                  | 04E.A142.H                  | 04E.A142.C    |
| Physical filtration process                          | Interception  | Interception+coal<br>escing | Interception+coal<br>escing | Adsorption    |
| Max solid dimension intercepted (ISO 8573-1)         | µm            | 5 µ                         | 1 µ                         | 0,01 µ        |
| Max solid dimension intercepted (ISO 8573-1)         | Class         | 3                           | 2                           | 1             |
| Remaining oil content after filtration (ISO 12500-1) | mg/m³         | //                          | 0,1 mg/m³                   | 0,01 mg/m³    |
| Remaining oil content after filtration (ISO 12500-1) | Class         | //                          | 2                           | 1             |
| Max temperature                                      | °C            | 100                         | 100                         | 100           |
| Pressure drop with new element                       | bar           | 0,05                        | 0,1                         | 0,1           |
| Pressure drop with saturated elements                | bar           | 0,4                         | 0,4                         | 0,4           |
| Element replacement time                             | hours         | 4000 h                      | 4000 h                      | 4000 h        |
| Element replacement time                             | months        | 6                           | 6                           | 6             |
|  |               |                             |                             | 3             |

| Line pressure [bar] | 1    | 2    | 3    | 5    | 7    | 9    | 11   | 13   | 15   | 16   |
|---------------------|------|------|------|------|------|------|------|------|------|------|
| Correction factor   | 0,38 | 0,53 | 0,65 | 0,85 | 1,00 | 1,13 | 1,25 | 1,36 | 1,46 | 1,51 |

| Dimensions (mm) |      |
|-----------------|------|
| A               | 1565 |
| B               | 885  |
| C               | 440  |
| D               | 300  |

