



# TECHNICAL DATA SHEET

ST 08U.2500BGA0

Rev. 00 Pag. 1/1

Date 28/02/2011

## DESICCANT DRYER

### MODEL

**HL2500PRO-70C**

### TYPE

**HEATLESS REGENERATION**

### OPERATING DATA

APPLICATION FLUID		AIR
NOMINAL CAPACITY	l/min	33333
	m <sup>3</sup> /h	2000
<b>NOMINAL CONDITIONS</b>	cfm	1178
PRESSURE RATE	bar	7
INLET AIR TEMPERATURE RATE	°C	35
PRESSURE DEW POINT	°C	- 70
RELATIVE HUMIDITY INLET AIR	%	100
PRESSURE DROP	bar	0,128
TYPICAL DRYING CYCLE COMPLETE	min	5
TYPICAL DRYING TIME FOR ONE COLUMN	min	2,5
REGENERATION AIR CONSUMPTION (NOMINAL FLOW RATE)	%	15

Without Energy Management System (EMS)

### OPERATING LIMITS

MINIMUM WORKING PRESSURE	bar	5
MAXIMUM WORKING PRESSURE	bar	10
MAXIMUM INLET AIR TEMPERATURE	°C	50
MINIMUM AMBIENT TEMPERATURE	°C	1
MAXIMUM AMBIENT TEMPERATURE	°C	50

### GENERAL DATA

AIR CONNECTION	IN/OUT	DN100	ISO 7/1
POWER SUPPLY	V/Ph/Hz	230/1/50	
DESICCANT MEDIUM		Alumina + Molecular Sieve	
ELECTRICAL PROTECTION		IP 54	
WEIGHT	kg	1350	

### DIMENSION

HEIGHT (A)	mm	2042
WIDTH (B)	mm	1981
DEPTH (C)	mm	1440

