



# TECHNICAL DATA SHEET

08U.1200GG.0

Rel.: 03 Sheet: 1/1

Date: 28/04/2021

## DESICCANT DRYER

### Model

**HLA1200 - 40°C**

### Type

**HEATLESS REGENERATION**

### Operating data

Application fluid		AIR
Nominal capacity	l/min	20000
	m <sup>3</sup> /h	1200
	cfm	706
<b>Nominal conditions</b>		
Working pressure	bar	7
Air inlet temperature	°C	35
Pressure dew point	°C	- 40
Inlet air relative humidity	%	100
Pressure drop	bar	0,27
Standard complete drying cycle time	min	10
Standard drying cycle time per column	min	5
Regeneration air consumption	m <sup>3</sup> /h	192

Without Energy Management System (EMS)

### Operating limits

Minimum working pressure	bar	5
Maximum working pressure	bar	10
Maximum inlet air temperature	°C	50
Minimum ambient temperature	°C	2
Maximum ambient temperature	°C	46

### General data

Air connections IN/OUT	IN/OUT	2"½ - 2"½ BSPP
Power supply	V/Ph/Hz	230/1/50-60
Desiccant medium		Alumina
Electric protection		IP 54
Weight	kg	805

### Dimensions

Height (A)	2475
Width (B)	1220
Depth (C)	710

