

# PPOG 1 - 120 - Oxygen generator with pressure swing adsorption technology

## Features & Benefits

- ▶ Energy saving control
- ▶ High-quality, high-efficient zeolite, selected for the right application
- ▶ Guaranteed purity
  - Zirconia sensors for reliable purity measurement
- ▶ Designed & tested for cyclic load
- ▶ Optimal control and monitoring thanks to Purelogic™ Controller
- ▶ Available with IEC and CSA/UL approvals

## General Specifications

- ▶ Pressure Swing Adsorption (PSA) Oxygen Generators - welded vessels
- ▶ Oxygen purity achievable: 90%-95%
- ▶ Inlet pressure range: 4-7.5 barg /58-109 psig
- ▶ Inlet temperature range: 5-45°C/41-113 psig
- ▶ Required inlet air quality: 1-4-1 according to ISO 8573-1:2010
- ▶ Power supply: 115-230VAC/50-60Hz



## Options



Seaworthy packaging



PDP sensor kit



Oxygen buffer vessels

Pneumatech gives oxygen to your business. With the PPOG range, Pneumatech offers an attractive replacement for traditional oxygen supply with very interesting returns on investment. The PPOG1-120 series uses Pressure Swing Adsorption technology to extract oxygen from compressed air, resulting in oxygen purity levels up to 95%.

The PPOG1-120 range is a welded vessel design, designed and tested for cyclic load. The Purelogic™ is the central brain of the generator. It optimizes operating costs thanks to the availability of the energy saving control; ensures maximum reliability by

monitoring the most important parameters of the generator; and offers impressive control and monitoring capabilities.

The calibrated flow meters are part of the standard scope of supply, in order to facilitate the start-up process and to provide transparency of the actual oxygen consumption. The optional oxygen buffer vessel is equipped with a pressure regulator, manometer and dust filter. Each of these components is approved for high-purity oxygen use. The optional inlet pressure dew point sensor provides additional security in case the upstream dryer would fail.

Technical specifications for PPOG 1-120																							
Specifications	Units	Product → Purity ↓	PPOG 1	PPOG 1.5	PPOG 2	PPOG 3	PPOG 4	PPOG 5	PPOG 6	PPOG 8	PPOG 11	PPOG 12	PPOG 14	PPOG 17	PPOG 20	PPOG 26	PPOG 33	PPOG 39	PPOG 50	PPOG 63	PPOG 93	PPOG 120	
Nominal free oxygen delivery <sup>(1)</sup>	Nm <sup>3</sup> /hr	90%	2.0	3.1	3.8	4.6	6.6	7.9	9.7	14.2	18.5	20.3	23.4	29.3	35.1	45.3	56.0	66.1	85.5	106.8	157.7	203.5	
		93%	1.6	2.5	3.5	4.3	5.6	7.3	9.0	13.4	18.3	19.3	21.4	27.6	33.0	42.7	51.9	64.1	79.4	101.7	154.6	188.2	
		95%	1.5	2.3	3.4	4.0	5.4	6.9	8.3	12.2	15.4	18.3	20.3	26.3	31.6	39.2	48.8	57.0	74.3	93.6	143.4	175.0	
Nominal air consumption	Nm <sup>3</sup> /hr	90%	22.6	30.5	36.6	54.9	73.3	103.8	103.8	157.5	192.3	219.8	256.4	329.6	366.3	518.9	634.8	799.6	982.8	1245.3	1867.9	2246.3	
		93%	22.0	29.9	36.0	53.7	67.1	100.7	102.6	146.5	189.2	213.6	244.2	319.9	355.3	512.8	604.3	781.3	964.5	1220.8	1953.3	2228.0	
		95%	21.4	28.7	35.4	51.9	65.9	97.7	102.6	140.4	170.9	207.5	238.1	313.1	347.9	500.5	586.0	763.0	915.6	1159.8	1892.3	2197.5	
Average air/oxygen ratio		90%	11.1	10.0	9.7	12.0	11.1	13.1	10.7	11.1	10.4	10.8	11.0	11.3	10.4	11.5	11.3	12.1	11.5	11.7	11.8	11.0	
		93%	13.5	11.8	10.4	12.6	12.0	13.8	11.5	10.9	10.3	11.1	11.4	11.6	10.8	12.0	11.6	12.2	12.2	12.0	12.6	11.8	
		95%	14.0	12.3	10.5	13.1	12.2	14.1	12.3	11.5	11.1	11.3	11.7	11.9	11.0	12.8	12.0	13.4	12.3	12.4	13.2	12.6	
Pressure dewpoint outlet (°C)	°C/°F		-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	
Oxygen outlet quality			ISO8573-1:2010 Class 1-2-1																				
Length	mm		600.0	600.0	750.0	750.0	850.0	850.0	1120.0	1120.0	1190.0	1230.0	1230.0	1640.0	1765.0	1960.0	1960.0	1960.0	2470.0	2920.0	2470.0	2920.0	
	inch		23.6	23.6	29.5	29.5	33.5	33.5	44.1	44.1	46.9	48.4	48.4	64.6	69.5	77.2	77.2	77.2	97.2	115.0	97.2	115.0	
Width	mm		757.0	757.0	770.0	770.0	848.0	848.0	875.0	875.0	924.0	943.0	947.0	1108.0	1135.0	1175.0	1175.0	1175.0	1305.0	1440.0	2610.0	2880.0	
	inch		29.8	29.8	30.3	30.3	33.4	33.4	34.4	34.4	36.4	37.1	37.3	43.6	44.7	46.3	46.3	46.3	51.4	56.7	102.8	113.4	
Height	mm		1467.0	1489.0	1801.0	1801.0	1630.0	1630.0	1962.0	1962.0	2252.0	2278.0	2678.0	2450.0	2492.0	3094.0	3094.0	3592.0	3097.0	3280.0	3097.0	3280.0	
	inch		57.8	58.6	70.9	70.9	64.2	64.2	77.2	77.2	88.7	89.7	105.4	96.5	98.1	121.8	121.8	141.4	121.9	129.1	121.9	129.1	
Mass	kg		193.8	226.8	324.8	330.6	412.6	412.6	723.0	735.0	1009.3	1192.3	1321.2	2359.3	2632.7	3150.0	3150.0	3681.0	4908.0	6489.0	9746.0	12470.0	
	lbs		427.3	500.0	716.1	728.9	909.6	909.6	1593.9	1620.3	2225.1	2628.5	2912.7	5201.4	5804.1	6944.6	6944.6	8115.2	10820.3	14305.8	21486.2	27491.6	
Inlet connections	G/NPT		G1/2"	G1/2"	G1/2"	G1/2"	G1/2"	G1/2"	G 3/4"	G 3/4"	G1"	G1"	G1"	G1 1/2"	G1 1/2"	DN50	DN50	DN50	DN50	DN50	2xDN50	2xDN50	
Outlet connections	G/NPT		G3/8"	G3/8"	G3/8"	G3/8"	G3/8"	G3/8"	G1/2"	G1/2"	G1/2"	G1/2"	G1/2"	G 3/4"	G 3/4"	G 3/4"	G 3/4"	G 3/4"	G 3/4"	G 3/4"	G 3/4"	2xG3/4"	2xG3/4"

1. Flow is measured at Reference Conditions: 1 bara and 20°C at operating pressure of compressed air of 6 barg and oxygen pressure at the outlet 4.5 barg, inlet temperature 20°C & Air Inlet Quality of ISO 8573-1:2010 class 1-4-1